



**GREENchoice™**  
ADHESIVES

## Acoustical Ceiling Tile Adhesive

Titebond® GREENchoice™ Acoustical Ceiling Tile Adhesive is designed for the safe and easy installation of acoustical ceiling tiles. Its fast, strong grab holds materials firmly in place and eliminates sagging. It offers excellent adhesion to common surfaces such as drywall, plaster, concrete and painted surfaces.

Acoustical Ceiling Tile Adhesive is environmentally superior and contains no ozone-depleting chemicals. It is nonflammable, emits no harmful fumes and cleans up with water. It also remains flexible and is unaffected by moisture.



### Product Features:

- For use on acoustical ceiling tiles
- Environmentally safe – VOC-compliant
- Fast grab – Excellent adhesion
- Nonflammable – No offensive odor
- “No sag” installation
- Water cleanup while wet

### Specifications:

- Meets ASTM D-1779\*
- Exceeds ASTM C557
- NFPA Class A fire rating when tested in accordance with ASTM E-84
- Passes California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010
- Meets with Collaborative for High Performance Schools (CHPS) low emitting material credit

\* For ceiling panel weight restrictions, please call our Help Line at 1.800.347.4583.



**GREENchoice™**  
ADHESIVES

This product is part of the Titebond GREENchoice family of professional-grade adhesives and sealants. Performance without compromise and integrity to preserving the environment are at the heart of every GREENchoice product. These high-performance products are formulated with environmentally superior technology for the toughest jobs. GREENchoice is backed by the same quality and support that you know and trust from Titebond.

**CertainTeed**  
SAINT-GOBAIN  
Ceilings

Endorsed and recommended by  
CertainTeed Ceilings



**GREENchoice™**  
ADHESIVES

# Acoustical Ceiling Tile Adhesive

## Physical Properties

**Type:** Polymer emulsion  
**State:** Medium-viscosity mastic  
**Color:** Beige  
**Solids:** 70%  
**Viscosity:** 200,000 cps  
**pH:** 5.0

**Calculated VOC:** 33.18 g/L  
**Weight/gallon:** 11.9 lbs.  
**Flashpoint:** >200° F.  
**Freeze/thaw stability:** Stable  
**Storage life:** More than 2 years in unopened container

## Application Guidelines

**Application temperature:** Over 50°F. for adhesive and substrates  
**Service temperature range:** 0°F. to 120°F.  
**Method of application:** Mason's trowel  
**Coverage:** 50-60 sq. ft. of ceiling tile per gallon  
**Working surfaces:** Surfaces must be dry and free from any material that may deter adhesion. Using the "butter" method, spread a thin layer of adhesive to cover a large area of each corner of the tile. Apply adhesive in 1" to 1 1/2" mounds (golf ball size). Place mounds 2-3 inches in from the corners on the back of the tile. Immediately press tile into position, working the tile back and forth 1/2" to flatten the mounds of adhesive. Adhesive must be flattened to a mound 3/16" to 3/8" thick and 2 1/2" in diameter. When installing interlocking tile, do not slide tile into groove of adjacent tile until it has been positioned to its proper level.  
**Cleanup:** Tools and excess adhesive may be cleaned with water while the adhesive is wet. If dried, tools and adhesive may be cleaned with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

## Product Features

- For use on acoustical ceiling tiles
- Fast grab - Excellent adhesion
- "No sag" installation
- Water cleanup
- Passes California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010
- Meets with Collaborative for High Performance Schools (CHPS) low emitting material credit
- Passes ASTM D-1779 specification\*
- NFPA Class A fire rating when tested in accordance with ASTM E-84

## Limitations

For best results, store Titebond GREENchoice Acoustical Ceiling Tile Adhesive above 50°F. Do not store product outside if temperature is below 50°F. Product must be stored inside a climate controlled area that is above 50°F. This product is recommended for use on tile sizes up to 12" x 12". It may be used on larger tiles, but instructions will differ. For information about tile sizes or for further questions about applications that are not covered here, please call our Help Line at 1.800.347.4583.

## Ordering Information

Part No.	Size	Weight	Units per Package	Packages per Pallet
2704	4 Gallon Pail	52.51 lbs.	1	36
2706	1 Gallon Pail	25.66 lbs.	2	75

\* For ceiling panel weight restrictions, please call our Help Line at 1.800.347.4583.

**Important Notice:** Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.