

All Weather 20°F - 120°F

SUBFLOOR

Construction Adhesive



Titebond® GREENchoice™ Subfloor Construction Adhesive is a professional strength formula that is specifically designed for subfloor installations and general plywood use. It provides a permanent bond that remains flexible, reduces nailing and helps prevent squeaky floors. The VOC-compliant, nonflammable formula is environmentally safe—emitting no harmful fumes and promoting healthy living and working environments.

GREENchoice Water-Based

- Environmentally safe
- Fills gaps & irregularities
- Highly water-resistant when dry
- Excellent aging qualities
- Offers freeze/thaw stability
- Cleans easily with water in wet state
- Cartridge & carton contain post-consumer recycled material
- Reduces nailing
- Excellent strength
- VOC-compliant

Recommended For

Subfloor installations, general plywood use, as well as filling gaps and irregularities in the subfloor.

Specifications & Certifications

Exceeds APA AFG-01 and ASTM C557.

Compatible Materials

Common building materials including wood, engineered lumber, particleboard, OSB and wet, frozen and treated lumber.



Titebond
THE PRO'S ADVANTAGE

Ordering/Sku Information

Size	Part Number	UPC	Case UPC	Weight	Units Per Package	Packages Per Pallet
28 Oz. Cartridge	4122	037083041224	10037083041221	30.02 lbs.	12	44
52 Gallon Drum	4128	NA	NA	566.06 lbs.	1	4

Technical Information

- **Application Temperature:** 20°F to 100°F
- **Service Temperature:** 0°F to 120°F
- **Working Time:** Approximately 20 minutes for a 1/4" bead

Physical Properties

- **Type:** Blend of polymer emulsions
- **State:** Medium-viscosity mastic
- **Color:** Off white
- **Solids:** 67.5%
- **Viscosity:** 82,500 cps
- **pH:** 7.5
- **VOC:** < 50 g/L
- **Weight/Gallon:** 10.64 lbs.
- **Flashpoint:** > 200°F
- **Freeze/Thaw Stability:** Stable
- **Storage Life:** 18 months in an unopened container

User Tips

Not designed for continuous submersion or for use on plastics or polyethylene foams. Do not adhere one non-porous material to another as this will slow or prevent drying.

Directions

PREP: Surfaces must be clean and free of any material that may prevent adequate adhesion.

APPLICATION: Cut tip straight across for 1/4" to 3/8" bead. Puncture inner seal and place in cartridge gun. Apply adhesive to each furring strip, stud or floor joist to be covered. **Adhere materials within 15 minutes or before skinning of adhesive occurs.** Position material to be bonded and press firmly for full contact with adhesive. **Note:** For subfloors, apply adhesive to joists for one sheet at a time. Nail or screw each sheet as recommended by the American Plywood Association.

CLEANUP: Tools and adhesive may be cleaned with water while the adhesive is wet. If dried, tools and adhesive may be cleaned with water/acetone/vinegar mixture. Follow solvent vendor's precautions.

Coverage

Size	1/8" bead	1/4" bead	3/8" bead
28 Oz. Cartridge	355 ft.	86 ft.	39 ft.

GREENchoice
Water-Based

Visit Titebond.com for the most up-to-date product information.

Franklin International



Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2019 01387_3776bcm FF1162

