

Faster. Stronger. Better.



Foamboard



Countertops



Landscaping



Subfloor

Titebond[®] THE PRO'S ADVANTAGE

Competitive Testing



Leading Competitor

▶ Wood to Wood (plywood to douglas fir)	951 psi	578 psi
▶ Frozen Lumber to Frozen Lumber	431 psi	200 psi
▶ Galvanized Steel to Lumber	97 psi	86 psi
▶ PVC to Poplar	428 psi	404 psi
▶ ABS to Poplar	315 psi	193 psi
▶ Cold Weather Extrudability	32° F	Above 40° F
▶ Shelf Life	18 months	12 months
▶ Odor	Low	Mild
▶ APA AFG-01	Pass	Pass
▶ ASTM D3498*	Pass	Pass
▶ ASTM C557	Pass	Pass
▶ CAN/CGSB - 71.26M	Pass	Not Listed
▶ CAN/CGSB - 71.25M	Pass	Not Listed
▶ Waterproof	Yes	Yes
▶ Flexible	Yes	No
▶ Drool	No	Yes
▶ Lifetime Subfloor Warranty	Yes	No

*Titebond Fast Set Polyurethane Construction Adhesive is the first to the market with passing results for ASTM D3498-19. Fast Set is a Class 1/8in., Type P/O subfloor adhesive in accordance with ASTM D3498-19.

Titebond®

THE PRO'S ADVANTAGE